UNCLASSIFIED

AD 288 125

Reproduced by the

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

288125

NOLTR 62-84

A MAGNETIC TAPE LIBRARY OF THERMODYNAMIC DATA

RELEASED TO ASTIA

BY THE-NAVAL ORDNANCE LABORATORY

- Without restrictions
- For Release to Military and Government Agencies Only.
- ☐ Approval by BuWeps required for release to contractors.
- Approval by BuWeps required for all subsequent release.

15 MAY 1962



UNITED STATES NAVAL ORDNANCE LABORATORY, WHITE OAK, MARYLAND

NOTICE: This material contains information affecting the national defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Sections 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

NOLTR 62-84

288 125

U.S. NAVAL ORDNANCE LABORATORY

WHITE OAK SILVER SPRING, MARYLAND

To all holders of NOLTR 62-84 insert change; write on cover 'Change 1 inserted' Approved by Commander, U.S. NOL

Change 1 10-1-62 1 page

By direction

This publication is changed as follows:

Page 11. After reference 18, add the following:

- 19. J. S. Martinez and G. W. Elverum, Jr., A Method of Calculating the Performance of Liquid Propellant Systems. Jet Propulsion Laboratory, Report 20-21 (Dec., 1955).
- 20. L. Brewer and A. W. Searcy, The Gaseous Species of the Al-Al₂0₃ System. J. Am. Chem. Soc. 73, 5308 (Nov., 1951).
- 21. Janaf Thermochemical Data 2 Vols., Dow Chemical Company (Dec., 1960) and Supplements.
- 22. Proceedings of the First Meeting, Janaf Thermochemical Panel, Publication No. T-1 (Nov., 1959).

Insert this change sheet between the cover and the title page of your copy.

A MAGNETIC TAPE LIBRARY OF THERMODYNAMIC DATA

Prepared by:

BERNARD A. BURKE CLARK P. LUCAS JOHN P. TOSCANO

ABSTRACT: This report describes the production and use of a magnetic tape library of thermodynamic data. The tape is produced from a deck of punched cards, six for each of more than one hundred chemical species. The data on each species include an identification number, coded references, formula, and atomic weight (of elemental species), the enthalpy change from 0°K to 298.15°K, the standard heat of formation at 298.15°K, melting point and heat of fusion, boiling point and heat of vaporization, coefficients giving the specific heat as a rational function of the temperature, and integration constants permitting calculation of enthalpy and entropy. All data are given for a pressure of one atmosphere. These data permit calculation of enthalpy, entropy and the Gibbs free energy over the temperature range 1000° - 6000°K. The machine program used in the work is presented accompanied by illustrations of its use. Sources of the original data are given. Examples are produced from the literature showing discrepancies for some aluminum and boron compounds. Future work will extend tape coverage to more than 350 species, allow for variation of the form of the specific heat function and provide for updating of the data tape.

PUBLISHED SEPTEMBER 1962

APPROVED BY:

D. Price, Acting Chief
Physical Chemistry Division
CHEMISTRY RESEARCH DEPARTMENT
U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, SILVER SPRING, MARYLAND

This report describes the construction of a magnetic tape library of thermodynamic data, for use with a high speed digital computer. The work was carried out as a part of the Naval Ordnance Laboratory's propellant development studies under Task PR-3, Propellant Formulation. The tape contains the data judged to be most reliable at the present time; it will be modified periodically to carry better data as they become available.

W. D. COLEMAN Captain, USN Commander

A. LIGHTBODY By direction

TABLE OF CONTENTS

| | | Page |
|---------------|---|------|
| INTRODUCTION | | 1 |
| THEORY | | 2 |
| DATA COLLECT: | ION | 4 |
| DATA CARD DEC | CK | 5 |
| MACHINE PROGR | RAM | 5 |
| RESULTS | • | 8 |
| FUTURE WORK | AND RECOMMENDATIONS | 8 |
| ACKNOWLEDGEM | ENT | 9 |
| REFERENCES . | • | 10 |
| APPENDIX A - | EQUATIONS USED BY THE PROGRAM | Al |
| APPENDIX B - | FORTRAN LISTING | Bl |
| | | |
| | ILLUSTRATIONS | |
| TABLE 1 | Arrangement of Species Data | 12 |
| TABLE 2 | List of Species on Tape | 13 |
| prompe 1 | Log K vs 1/T for the Reaction of | |
| FIGURE 1 | Al ₂ 0 ₃ (1) and H ₂ (g) | 14 |
| FIGURE 2 | Information on Data Card No. 1 | 15 |
| FIGURE 3 | Information on Data Card No. 2 | 16 |
| FIGURE 4 | Information on Data Card No. 3 | 17 |
| FIGURE 5 | Information on Data Cards Nos. 4, 5, and 6 | 18 |

ILLUSTRATIONS (Cont'd)

| | | <u>.</u> <u>P</u> | age |
|--------|----|----------------------------------|-----|
| FIGURE | 6 | Block Diagram of Machine Program | 19 |
| FIGURE | 7 | Input Cards for Option(2) | 20 |
| FIGURE | 8 | Output from Option (2) | 21 |
| FIGURE | 9 | Input Cards for Option (-1) | 22 |
| FIGURE | 10 | Output from Option (-1) | 23 |
| FIGURE | 11 | Input Tape Listing (A) | 24 |
| FIGURE | 12 | Input Tape Listing (B) | 25 |
| FIGURE | 13 | Input Cards for Option (1) | 26 |
| FIGURE | 14 | Input Cards for Option (3) | 27 |

INTRODUCTION

The results presented in this report are a by-product of the Naval Ordnance Laboratory's effort in the field of rocket propellant research. Although taped thermodynamic data can be used for other problems, the tape was made specifically for use with a program developed here to compute the theoretical performance parameters of solid rocket propellants. As is well known, the computation of specific impulse and other characteristic parameters of a propellant involves the use of large amounts of data for many chemical species; to be most useful for machine computation these data should be easily accessible, and amenable to simple modification if improved values are received. With the present state of the computer art, the use of a magnetic tape best fulfills the above requirements. Accordingly the objective was to collect, verify and collate thermodynamic data, and store them on a magnetic tape in a practical, accessible form.

For making the tape, the data fall into two categories: part, such as heats of formation, can be read onto the tape immediately after verification, while the remainder, such as specific heats, must be reduced to a form suitable for tape storage. Early workers tended to store data tables, giving values at discrete temperature values. Such data required interpolation for intermediate temperatures. A better practice is to reduce the data by a curve fitting process to a rational function of the temperature and store only the coefficients of the function. A Fortran language program, to be discussed later, was written and compiled to do this as well as other parts of the data work. After collection and preparation, the data were punched on cards and subsequently written onto an IBM magnetic tape. In this form they may be readily recalled for further work by the IBM 704 or 7090 computers. Sample Data Program output sheets are illustrated and discussed in the body of the report.

The various data sources searched agree with each other within one percent for the common compounds of carbon, hydrogen, nitrogen and oxygen and the common halides. In some cases, particularly with newer types of propellant ingredients e.g..

^{*}This program has been in operation since March 1960. It will be described in a forthcoming report.

light metals, the necessary data are not in final form as shown by the lack of agreement among competent workers in the field. Again, evidence of new species stable at high temperatures is being found and for these the data are still in the preliminary stage. More refined studies must be made on some ternary and higher compounds.

Although a data sheet has been printed out for verification for each species on the tape, it is not the intention here to add another member to the already large, and still growing list of published collections of thermodynamic data. Since most of these lists go back to a relatively few common sources such as reference (1), they represent duplication of effort in the case of the well known species and multiplication of inaccurracies in the case of newer ones. The latter require further effort to eliminate inaccurracies; discussion and selection of such data are better included in reports of work utilizing the particular quantities. For example, reported theoretical specific impulses should always be accompanied by input data on any questionable species considered in the calculations.

In the meantime, since there are differences between one laboratory and another in the calculational methods used, it would be helpful if all groups at least used common data. The JANAF Thermochemical Panel has undertaken the ambitious task of bringing this about; and one of the final objectives of the present work is to bring the data library tape into accord with the JANAF Thermochemical Tables. Further, coverage is being extended from 103 to about 350 chemical species and the program is being modified to allow more latitude in the treatment of specific heats and other data.

THEORY

As noted in Section I, the data to be recorded were divided into two parts: those to be taped immediately and those to be reduced first to a set of storable parameters. They were assembled mainly from the sources given by references 1 to 11. Data such as heats of formation, melting and boiling points were collected, verified, punched on IBM cards and read directly onto the magnetic tape.

For data from which thermodynamic functions were to be derived, the procedure was different; the items to be stored on

tape for each species were: coefficients of a function of the temperature, T, which defined the specific heat, C_p, at a pressure of one atmosphere, and two integration constants, H and S', discussed below. From these data by the application of elementary thermodynamics, the enthalpy H, the entropy S and the Gibbs free energy G were derived.

Since Cp, an experimental quantity put into an appropriate analytical form, has to be integrated to obtain the enthalpy, it has to be represented by some function of T; and no one function provides a representation equally good for all chemical species. As pointed out by Maier and Kelley (12) it was at one time common practice to represent the enthalpy by an elementary power series in T, terms as high as T3 usually being taken. Differentiation then resulted in a quadratic function for Cp which could, ".... have a maximum in the temperature range under consideration due to the signs and magnitudes of the coefficients, but such a maximum does not correspond to known physical facts" They proposed the addition of negative powers of the temperature, and showed by comparative results the improvement obtained over the simple quadratic function. Since then several different functions have been employed, with varying success, to represent C_D(T) analytically. The form used here was noted in a Wright Air Development Center report (13), and has since been used in the preparation of the JANAF Thermochemical Tables (21). For all species they use the function

$$C_p = C_p(T) = a + b\theta + c\theta^2 + d\theta^3 + e\theta^{-2}$$
 (1)

where, for convenience

$$\Theta = 10^{-3} \text{ T} \tag{2}$$

The problem was then to determine the set of parameters a, b, c, d and e for each chemical species. Obviously five equations were needed and these were obtained by using experimental values of $C_{\rm p}$ at five different temperatures. There resulted a set of five equations linear in a, b, c, d and e, and these were solved readily using a simple matrix inversion technique.

With a, b, c, d and e known for a species, $C_{\rm p}$ was defined; for the enthalpy and entropy, it remained only to determine the integration constants H' and S' respectively. The elementary

steps needed are summarized in Appendix A, and a detailed example was presented in reference (13). The variation of H' and S' was shown to be approximately 1% between 1000° and 6000°K. This was considered tolerable.

DATA COLLECTION

Although several score sources have been examined in the process of collecting thermodynamic data, only a few of the more important ones are referenced here (1-11). Of these, the most important were from the National Bureau of Standards (1, 4, 6, 7). The reference states of the elements were taken as given by Stull and Sinke (10).

Among the data in use, good agreement exists between one laboratory and another for the common compounds of carbon, hydrogen, nitrogen and oxygen, and also of fluorine and chlorine. However, when metallic combustion products are considered, agreement is often lacking between one laboratory and another. Present knowledge of these compounds has been summarized by Dobbins (9), pages 99 et seq; and Gilles (14) has reviewed the status of work on high temperature ternary species, another area where general agreement is lacking. It is necessary here only to present a few illustrative examples of variation in data used.

Fig. 1 shows three derived curves * of common log K vs 1/T for the reaction

$$Al_2O_3(1) + 2H_2(g) \iff Al_2O(g) + 2H_2O(1).$$

The upper and lower curves represented the extreme values among those based upon material in several classified and unclassified sources (2, 16, 17, 18, 19, 20). Since the scale on the ordinate represented powers of ten, the graph illustrated the large differences from one laboratory to another. The third curve shown was based upon values which are now considered acceptable, and are reported in the open literature (21).

^{*}Before the publication of reference (15), flame temperatures and compositions were computed here using the older equilibrium constant method, thus the interest in log K. Although the method is no longer used, the results shown in Fig. 1 are typical of the kind of disagreement often found.

Another example is the standard heat of formation of boron nitride. This has been variously reported (in kcals per mol) as 131.4 (5), 155 (9) and 158.1 (1). Again the existence of a boron subchloride BCl₂ has been inferred (9) from the existence of the dimer; and the heat of formation of the subchloride has been reported as -24.6 (5) and -82.0 (9).

In cases such as these, the consistency of the given data with other known values for the species was checked. Until recently (See Recommendations) values given by the National Bureau of Standards were considered to be the most acceptable in cases which could not otherwise be decided. Henceforth, values from the JANAF tables will be used.

DATA CARD DECK

Six IBM cards are used to hold the data for each species prior to taping them. The first three cards (of the set of six) contain thermodynamic data and are described in Figs. 2, 3 and 4. Fig. 5 typifies the last three cards of the set. The summary of data for one species is indicated in Table 1. In this table the lower case letters, "cc" in the left hand column stand for, "card column" and define the card fields. The center column of the table lists the information in the corresponding card columns. The column on the right side of the table gives the storage designations for the data when they are being used. The letters SPD in this column originally meant Species Data, and are now used to identify all data storage designations.

The data for the first three cards of a set may be punched as soon as verified. The last three cards, typified by Fig. 5, refer to the gas (card 4), liquid (card 5) and solid (card 6) phases of a species. Each of these three contains seven numbers. The first five are respectively the coefficients a, b, c, d and e for the species and the last two are the corresponding integration constants H' and S', for the enthalpy and entropy respectively.

MACHINE PROGRAM

On page three and Appendix A equations are presented for the specific heat at constant pressure, the enthalpy, the entropy and Gibbs free energy as functions of temperature. A Fortran program was written to derive the coefficients of the Cp equation and to compute tables of these functions. A block diagram of the program is shown in Fig. 6 and a copy of the Fortran listing is included as Appendix B.

Five options were built into the program, including one "dummy" for future use. The options have extended the program's usefulness. According to the job to be done, the proper option number was punched on a card and the program followed the indicated path. A description of the various options follows, in logical rather than numerical order.

Option (2). When new experimental C_p data were acquired, we wished to find the coefficients of the C_p function. The cards were punched as shown in Fig. 7. This option caused the program to compute a, b, c, d, e, H' and S', and print-out the results for inspection. Figure 8 is a sample of the print-out for this option showing the input C_p , H and S and the resulting set of constants.

Option (-1). If the data table derived from the above computed coefficients was desired, the cards for this option were punched as shown in Fig. 9 and used in conjunction with option (2). A sample of this output is shown in Fig. 10. The machine time for the example shown was approximately five seconds on the IBM 704.

Now if examination showed an error in the above table (Fig. 10) it was corrected at this point. If, however, the data were consistent with other known data, the new coefficients were punched on card No. 4, 5 or 6 for this species, depending upon the phase being considered and were now ready to be read onto the tape. In this way, the tape library was compiled. The tape is kept in the computer room, and the corresponding card deck is kept for use in future modifications of the tape.

Figures 11 and 12 illustrate the arrangement of the data on tape. It is exactly as the data card deck is read in. Fig. 11 shows the first cards (of each set of six) for several species. The identification numbers are in the left hand column, and the first forty rows were reserved for atomic species. A figure one occurs in the column corresponding to the identification number of the atomic species, i.e., row 12 has a one printed in column 12, row 14, a one printed in column 14, etc. This permitted a simple method of defining molecular types, which occupy the rows beyond number forty. For example, a one in row 7 identifies atomic hydrogen and a one in row 11 identifies atomic oxygen. So in order to specify a molecule of

H₂O (row 45), a 2 was placed in column 7 and a 1 in column 11. The assignment of a column to a particular element allowed efficient formulation of molecular species on tape. Upon recall of the data a Symbol Sub-routine identified the numbers in each row and converted them to atomic formulae. The remaining information (right hand columns of Fig. 12), includes the weights, given for atomic species only, and a set of numbers giving the references for each species.

Fig. 12 is a section of the print-out corresponding to the last five data cards for each of nine separate species. What appears are three rows for each species, corresponding to data cards 2, 3 and 4. This is because the species here listed do not have liquid (card 5) or solid (card 6) phases at the temperatures being considered. The full row in each group, shows in order a, b, c, d, e, H' and S' for the gas phase. If liquid or solid phases for any of these species were present, they would be placed in the two rows immediately below that for the gaseous phase. This option has been useful when a problem result indicated a possible error on the tape. It provides for fast checking.

Option (1). When it was desired to examine the tape contents, the input cards were punched as in Fig. 13. The print-out from this option consists of the taped information discussed above, listed with proper English column headings. It has been a convenient means of examining the tape contents.

Option (3). As in the other options, the cards used here (Fig. 14) were simple to prepare. The data tables for any species (Fig. 10), or chosen group of species, were obtained as the specific impulse program uses them. When desired, this option can print data tables for all the species on tape; such tables are in suitable form for publication.

In using the program, data cards are punched according to the appropriate figures for each option. The cards are then placed at the end of the program deck and run into the card hopper. Obviously, Options (-1) and (2) operate directly from card input, while (1) and (3) require that a data tape reel be placed on tape unit No. 7, the data input unit of the 704 computer. For the IEM 7090, the tape number is A7. If by the use

of Options (-1) and (2), acceptable species data have been generated, they are punched onto card 4, 5 or 6, and inserted into the library deck along with the first three cards for the species. In this way data on any species in the library deck can be replaced.

The library deck and the tape are the end results of the work. The program deck, used to handle the data, may be reproduced simply by punching the cards shown in the Fortran listing of Appendix B. After this program deck is compiled, it is necessary only to choose an option in order to use the system. Table 2 is a list of the 103 species for which data are on tape.

RESULTS

A continuing system has been set up for the acquisition, verification and recording on magnetic tape, of thermodynamic data. Methods have been developed for replacing data now on tape, and for adding data on new species. This work has been carried on simultaneously with work on the theoretical propellant calculation program so that a modicum of data was available as soon as the latter was ready to be tested. Much information has since been added to the library, and it has been used successfully for hundreds of propellant calculations. The Laboratory has not essayed the publication of a data book because the already long list of such books precludes further duplication. However, a print-out of the material on the tape has been made for our own use, and the latest tape revision occurred in May 1961.

It may be noted that the present method of storing thermodynamic data is a considerable improvement over older methods. Stored data tables are too unwieldy since it is at times desirable in a calculation to consider as many as 20 - 30 chemical species and the necessary table storage space is too large, even for modern memory devices. Besides this, the storage of data tables requires the use of interpolation subroutines since the occurrence of a temperature value lying between two of those given in the table is inevitable.

FUTURE WORK AND RECOMMENDATIONS

A better method of curve fitting might be used in the Fortran program. A least squares fit and Tchebicheff Polynomials are both being considered. Certain techniques which heretofore have been separate from the data program should be

assimilated into it as further options. For example, one separate program computes the coefficients a, b, c, d and e in equation (1) from coefficients as given by other C_p equations for the same species; while another program prints out all the data available at any given temperature, as a single block of information. Further, techniques are now available for providing relatively automatic updating of the tape. These techniques would allow an even simpler method of tape modification.

Since many species of great importance in rocket propellant calculations are still not completely defined, a continuing data search should be made for the most probable values among those available for these species.

In the past, the National Bureau of Standards data has been used as the most reliable. In the interest of furthering consistency among all groups in the field, the data used by this Laboratory should be based upon the data published by the JANAF Thermochemical Panel (21, 22). Revisions of these data are continually being supplied by the Panel; so the fact that the data in many cases is admittedly tentative should not be a deterrent.

Finally it would be of considerable interest to extend this work in the direction of more extreme thermodynamic conditions because of its potential use in explosives computations.

ACKNOWLEDGEMENT

Mr. William Evans of the Thermodynamics Division of the National Bureau of Standards has discussed parts of the work with the authors. Of those at the Naval Ordnance Laboratory, we are especially indebted to Dr. E. C. Noonan (deceased) and Dr. D. Price for critical appraisals of data on certain chemical species, and to Dr. Price and Mr. J. Enig for critical reading of the manuscript. In the Mathematical Computations Division the cooperation of Mr. H. Stevens and the IBM 704 Machine Operators has been appreciated; and without the very patient efforts of Mrs. Helena Hall, the transfer of data to punched cards would have been a much more painful process than it actually was. Finally, our thanks to Mrs. Mildred Ward for the typing of drafts and manuscripts.

REFERENCES

- 1. F. D. Rossini, D. D. Wagman, W. H. Evans, S. Levine and I. Jaffe, Selected Values of Chemical Thermodynamic Properties. National Bureau of Standards, Circular 500. Series I and II (1952) and Series III (1956).
- 2. V. N. Huff, S. Gordon, and V. E. Morell, General Method and Thermodynamic Tables for Computation of Equilibrium Composition and Temperature of Chemical Reactions. NACA Report 1037 (1951).
- 3. J. S. Gordon, Thermodynamics of High Temperature Gas Mixtures, and Application to Combustion Problems. WADC Report 57-33 (Jan. 1957).
- 4. W. H. Evans, D. D. Wagman and E. J. Prosen, <u>Thermodynamic</u> Properties of Some Boron Compounds. National Bureau of Standards Report 4943 (Aug. 1956).
- 5. J. S. Gordon, Thermodynamic Data for Combustion Products. Thiokol Report RMD 210-ES (Jan. 1960).
- 6. C. W. Beckett, Preliminary Report on the Thermodynamic Properties of Lithium, Beryllium, Magnesium, Aluminum, and Their Compounds with Oxygen, Hydrogen, Fluorine and Chlorine (Revised). National Bureau of Standards Report 6297 (Jan. 1959); Supplement, Report 6484 (July, 1959).
- 7. C. W. Beckett, Preliminary Report on the Thermodynamic Properties of Selected Light Element Compounds (Supplement to NBS Reports 6297 and 6484 (Jan. 1960); Supplement Report 6928 (July 1960); Supplement Report 7093 (Jan. 1961).
- 8. K. K. Kelley, Contributions to the Data on Theoretical Metallurgy. U.S. Dept of the Interior, Bureau of Mines, Bulletin 383 (1935), 476 (1949), 477 (1950).
- 9. T. O. Dobbins, Thermodynamics of Rocket Propulsion and Theoretical Evaluation of Some Prototype Propellant Combinations. Wright Air Development Center, Project 3148 (Dec. 1959).
- 10. D. R. Stull and G. C. Sinke, Thermodynamic Properties of the Elements. Advances in Chemistry Series No. 18, American Chemical Society, Washington 6, D.C. (Nov. 1956).

REFERENCES (Cont'd.)

- 11. L. L. Quill, The Chemistry and Metallurgy of Miscellaneous Materials Thermodynamics. National Nuclear Energy Series, Division IV Plutonium Project Record Vol. 19B, McGraw-Hill (1950).
- 12. C. G. Maier and K. K. Kelley, An Equation for the Representation of High Temperature Heat Content Data.

 J. Am. Chem. Soc., 54, 3243 (1932).
- 13. Research on Solid Fuels and Oxidizers, Progress Report
 No. 2. Wright Air Development Center (Dec. 1958).
 Confidential.
- 14. P. W. Gilles, <u>Ternary Species at High Temperatures</u>.

 XVIII International Symposium of Pure and Applied Chemistry, Sessional Lecture A3-13, Montreal, Canada (Aug. 1961).
- 15. White, Johnson and Dantzig, J. Chem. Phys. 28, 751 (1958).
- 16. Report No. P57-4, Project No. TJZ-10, Ordnance Corps, Department of the Army (Dec. 1956 Feb. 1957). Confidential.
- 17. Theoretical Performance of Selected Propellant Systems, I:

 Aluminum As a High Energy Ingredient, United States Navy
 Bureau of Ordnance (July, 1958). Confidential.
- 18. Study of Metal Additives for Solid Propellants, United States Navy Bureau of Ordnance (Jan. 1958). Confidential.


TABLE 1
Arrangement of Species Data


| Card | Card Columns | Data | Tape |
|------|---|---|---|
| I | cc 1 3 cc 4 43 cc 44 53 cc 54 (0.1) cc 55 (1,) | ID Number Formulation Mol. Wt. Phase Ref. | SPD (I,1) Not Stored SPD(I,2) SPD(I,3) Not Stored |
| II | cc 1 10 | $\Delta H_{\mathbf{f}}^{298}$ (g) | SPD(I,4) |
| | cc 11 20 | $\Delta H_{\mathbf{f}}^{298}$ (1) | SPD(I,5) |
| | cc 21 30 | ΔH ²⁹⁸ (в) | SPD(1,6) |
| | cc 31 40 | bp | SPD(I,7) |
| | cc 41 50 | mp | SPD(I, 8) |
| III | cc 1 10 | $H_{298}-H_{0}$ (g) | SPD(I,9) |
| | cc 11 20 | $H_{298}-H_{0}$ (1) | SPD(1,10) |
| | cc 21 30 | H ₂₉₈ -H _o (s) | SPD(1,11) |
| | cc 31 40 | ΔH _V (vaporizatio | SPD(I,12) |
| | cc 41 50 | $\Delta H_{\hat{\mathbf{I}}}(\text{fusion})$ | SPD(I,13) |
| IV | cc 1 10 cc 11 20 cc 21 30 cc 31 40 cc 41 50 cc 51 60 cc 61 70 | a(g) b c d H' 2S | SPD(I,14) SPD(I,15) SPD(I,16) SPD(I,17) SPD(I,18) SPD(I,19) SPD(I,20) |
| ٧ | cc 1 10 cc 11 20 cc 21 30 cc 31 40 cc 41 50 cc 51 60 cc 61 70 | a(1) b c d e lH' 2S' | SPD(I,21) SPD(I,22) SPD(I,23) SPD(I,24) SPD(I,25) SPD(I,26) SPD(I,27) |
| VI | cc 1 10 cc 11 20 cc 21 30 cc 31 40 cc 41 50 cc 51 60 cc 61 70 | a(s) b c d e H' | SPD(I,28) SPD(I,29) SPD(I,30) SPD(I,31) SPD(I,32) SPD(I,33) SPD(I,34) |

TABLE 2
List of Species on Tape

| Al | HF | CF | BC1 | LiCl |
|------------------|------------------|--------------------------------|------------------------------------|-----------------------|
| A1(1) | ^{C1} 2 | CF ₂ | BCl ₂ | LiF |
| B | ClF | CF ₃ | BC13 | LiH |
| Be | HC1 | CF ₄ | BF | LiO |
| C | C10 | C ₂ F ₂ | BF ₃ | L1 ₂ 0 |
| C(s) | S ² 2 | сғ ₃ н | BH | Lioh |
| Cl | HS | CH ₂ F ₂ | EN | A1 ₂ 0 |
| F | SO | CH ₃ F | BN(s) | AlF ₃ |
| Н | N ₂ | coŕ ₂ | BO | AlF ₂ |
| Li | NFO | СН | B ₂ 0 ₂ | AlfO |
| Mg | NH | CH ₂ | B ₂ 0 ₃ | AlCl ₃ |
| N | NO | СH ₄ | AlF | A1C1 ₃ (1) |
| 0 | P ₂ | CN | AlH | AlCl2 |
| P | P4 | $c_2 n_2$ | AlO | AlClo |
| S | PH - | CNF | Al ₂ 0 ₃ (1) | AlClF ₂ |
| Si | PH ₃ | CO | Al ₂ 0 ₃ (s) | AlClF |
| 02 | PN | co ₂ | BeF ● | AlCl |
| 0, | PO | COH ₂ | Вен | AlC |
| H ₂ | c ₂ | CP | Be0 | AlF |
| OH | c ₃ | CS | MgF | AlS |
| H ₂ 0 | CCl | SiO | MgH | |
| F ₂ | COC12 | B ₂ | Li ₂ | |
| | | | _ | |

NOTE: All species are gaseous unless noted, in which cases an s or l in parenthesis indicates the solid or liquid phase respectively.





NOTE : THIS CARD IS COLORED BLUE.


INFORMATION ON DATA CARD NO. I FIG. 2

| /- | | | | |
|------------------|----------------------------------|---|--------|-------|
| / 92 | | BLANK | | |
| 72 ++176 | 27 – ET | # 01 | | |
| | BLANK | 8 | | |
| <u>-</u> 50,51 - | | O | | • |
| | d E | IF ZERO SPECIES WILL ALWAYS BE CONSIDERED A LIQUID | OR GAS | |
| 31 | d q | IF ZERO SPECIES WILL ALWAYS BE CONSIDERED A GAS | | |
| 30,31 | 298 (£) | | | |
| 214 | ΔH ² | | | |
| 1120 21- | ΔH _f 298 (1) | | | |
| 101 | ΔH _ξ (g) | | | |
| -1 | | | | |

NOTE: THIS CARD IS COLORED YELLOW.

DECIMAL POINT PUNCHED FOR EACH DATUM.


FIG. 3 INFORMATION ON DATA CARD NO. 2



NOTE: THIS CARD IS COLORED YELLOW.

DECIMAL POINT PUNCHED FOR EACH DATUM.

FIG. 4 INFORMATION ON DATA CARD NO. 3



NOTE: THESE CARDS ARE COLORED YELLOW.


DECIMAL POINT PUNCHED FOR EACH DATUM.

CARD NUMBER 4 IS FOR GAS PHASE.

CARD NUMBER 5 IS FOR LIQUID PHASE.

CARD NUMBER 6 IS FOR SOLID PHASE.

FIG. 5 INFORMATION ON DATA CARDS NOS. 4, 5 AND 6



19

THREE CARDS ARE USED FOR THIS OPTION

Card No. 1:

cc 2, punch: 2

Card No. 2:

punch: \triangle coefficient \triangle determination \triangle for H_2O \triangle formula (atomic formula of species)

Card No. 3:

cc 1-10 punch: C_p(1000)

cc 11-20 punch: C_p(1600)

cc 21-30 punch: C_D(3000)

cc 31-40 punch: C_D(4500)

cc 41-50 punch: C_p(5700)

cc 51-60 punch: H'(3000)

cc 61-70 punch: S'(3000)

Note: On Card No. 2 4 represents a blank. cc means card column.

Fixed point: decimal point must be punched.

Figure 7 - Input Cards for Option (2)

-7.03557E-01

d.26448E-02

COEFFICIENT DETERMINATION FOR H20(g)

| 5700 | 14.351 |
|--------------------|--------|
| 4500 | 14.030 |
| 3000 | 13.304 |
| 1600 | 11.462 |
| 1000 | 9.851 |
| MATCH TEMPERATURES | CP |

(H(3000)-H(0))/3000 = 10.856S(3000) = 68.421 7.74325E 00 3.40507E 00 6.36411E-01

NOTE: TRIAL COEFFICIENT DETERMINATION BASED UPON DATA FROM JANAF THERMOCHEMICAL TABLES; IN THIS CASE, ENTHALPY AND ENTROPY VALUES WERE TAKEN ONLY AT 3000° K

FIG.8 OUTPUT FROM OPTION 2

TWO CARDS ARE USED FOR THIS OPTION

Card No. 1

cc 1, 2 punch: -1

Card No. 2

cc 1-10 punch: Ti

cc 11-20 punch: T_f

cc 21-30 punch: T

NOTE: T_i and T_f are the lower and upper limits of the temperature interval over which data are desired. This the size of the step from T_i to $T_{(i+1)}$

NOTE: Fixed point: decimal point must be punched.

Figure 9 - Input Cards for Option (-1)

NOLTR 62-84

THERMODYNAMIC DATA FOR H2O GAS

| | СР | (H-H _{o.})/T | S | (G-G _o)/T |
|------------------------|--------------|------------------------|-------------|-----------------------|
| Ť | (CALS/ | (CALS/ | (CALS/ | (CALS/ |
| (^O Kelvin) | MOL °K) | MOL °K) | MOL °K) | MOL ^o K) |
| 1000. | 9.85026E 00 | 8.57754E 00 | 5.55906E 01 | -4.70131E 01 |
| 1100. | 1.01561E 01 | 8.70725E 00 | 5.65149E 01 | -4.78077E 01 |
| 1200. | 1.04474E 01 | 8.84023E 00 | 5.73839E 01 | -4.85437E 01 |
| 1300. | 1.07229E 01 | 8.97455E 00 | 5.82045E 01 | -4.92299E 01 |
| 1400. | 1.09823E 01 | 9.10880E 00 | 5.89822E 01 | -4.98734E 01 |
| 1500. | 1.12256E 01 | 9.24190E 00 | 5.97214E 01 | -5.04795E 01 |
| 1600. | 1.14530E 01 | 9.37307E 00 | 6.04258E 01 | -5.10527E 01 |
| 1700. | 1.16649E 01 | 9.50172E 00 | 6.10983E 01 | -5.15966E 01 |
| 1800. | 1.18619E 01 | 9.62744E 00 | 6.17414E 01 | -5.21140E 01 |
| 1900. | 1.20444E 01 | 9.74991E 00 | 6.23574E 01 | -5.26075E 01 |
| 2000. | 1.22132E 01 | 9.86891E 00 | 6.29481E 01 | -5.30792E 01 |
| 2100. | 1.23689E 01 | 9.98430E 00 | 6.35151E 01 | -5.35308E 01 |
| 2200. | 1.25122E 01 | 1.00960E 01 | 6.40598E 01 | -5.39639E 01 |
| 2300. | 1.26439E 01 | 1.02039E 01 | 6.45837E 01 | <i>-5</i> .43797E 01 |
| 2400. | 1.27646E 01 | 1.03082E 01 | 6.50877E 01 | -5.47796E 01 |
| 2500. | 1.28752E 01 | 1,04087E 01 | 6.55731E 01 | -5.51644E 01 |
| 2600. | 1.29765E 01 | 1.05055E 01 | 6.60406E 01 | -5.55351E 01 |
| 2700. | 1.30691E 01 | 1.05988E 01 | 6.64913E 01 | -5.58926E 01 |
| 2800. | 1.31539E 01 | 1.06885E 01 | 6.69259E 01 | -5.62374E 01 |
| 2900. | 1.32316E 01 | 1.07749E 01 | 6.73452E 01 | -5.65703E 01 |
| 3000. | 1.33032E 01 | 1.08580E 01 | 6.77499E 01 | -5.68919E 01 |
| 3100. | 1.33692E 01 | 1.09380E 01 | 6.81406E 01 | -5.72026E 01 |
| 3200. | 1.34306E 01 | 1.10149E 01 | 6.85180E 01 | -5.75031E 01 |
| 3300. | 1.34881E 01 | 1.10890E 01 | 6.88826E 01 | -5.77937E 01 |
| 3400. | 1.35425E 01 | 1.11604E 01 | 6.92351E 01 | -5.80748E 01 |
| 3500. | 1.35947E 01 | 1.12292E 01 | 6.95760E 01 | -5.83468E 01 |
| 3600. | 1.36453E 01 | 1.12956E 01 | 6.99058E 01 | -5.86102E 01 |
| 3700. | 1.36954E 01 | 1.13598E 01 | 7.02249E 01 | -5.88651E 01 |
| 3800. | 1.37455E 01 | 1.14219E 01 | 7.05339E 01 | -5.91120E 01 |
| 3900. | 1.37966E 01 | 1.14821E 01 | 7.08332E 01 | -5.93511E 01 |
| 4000. | 1.38494E 01 | 1.15406E C1 | 7.11233E 01 | -5.95826E 01 |
| 4100. | 1.39047E 01 | 1.15976E 01 | 7.14045E 01 | -5.98069E 01 |
| 4200. | 1.39634E 01 | 1.16532E 01 | 7.16774E 01 | -6.00242E 01 |
| 4300. | 1.40263E 01 | 1.17077E 01 | 7.19424E 01 | -6.02347E 01 |
| 4400. | 1.40941E 01 | 1.17611E 01 | 7.21997E 01 | -6.04386E 01 |
| 4500. | 1.41676E 01 | 1.18138E 01 | 7.24499E 01 | -6.06361E 01 |

NOTE: Given the necessary coefficients, compute and print data table for species named, from $1000^\circ K$ to $6000^\circ K$.

FIG. 10 PARTIAL OUTPUT FROM OPTION (-1)




FIG. II INPUT TAPE LISTING (A)

NOLTR 62-84

| CARD NO. | | | | | | | |
|-------------|--------------------|--------------------------|------------|---------|---------------|----------------|----------|
| 2 | 121600. | | | | | | |
| 3 | 2250. | | | | | | |
| 4 5 | 8.91979 | 0.04404 | -0.0024 | 0.00017 | -0.19660 | -0.9700 | 63.8156 |
| 6 2 | -53300. | | | 264.7 | | | |
| 3 | 3283. | 1 01400 | 00710 | 00701 | 72650 | -4.3637 | 00 0400 |
| 4 5 6 | 18.5699 | 1.01499 | 28713 | .02781 | 73558 | -4,303/ | 88.2420 |
| 2 | 74500. | | | | | | |
| 2 | 2170. | | | | | | |
| 4 5 | 8.59423 | 0.36810 | -0.08798 | 0.00895 | -0.34429 | -1.3240 | 59.8720 |
| 6 | 2000 | | | | | | |
| 2 3 | - 30000. | | | | | | |
| 3 4 | 2467. 13.52244 | 0.24640 | -0.05383 | 0.00372 | -0.87872 | -3.9585 | 70.2310 |
| 5 | 15,52244 | 0.24040 | -0,00363 | 0.00072 | -0.0/0/2 | -3.7500 | 70.2010 |
| . 6 | | | | | | | |
| 2 | -120500. | | | | | | |
| 3 | 2794. | | | | | | |
| 4 | 18.97333 | 0.70465 | -0.20308 | 0.02012 | -1.2850 | -6.4394 | 79.8664 |
| 5 | | • | | | | | |
| 6 | | | | | | | |
| 2 | -218000. | | | | | | |
| 3 | 3045. | 0 07001 | 0.05405 | 0.00500 | 1 74070 | 0.0157 | 0.4 0070 |
| 4 | 24.72236 | 0.87981 | -0.25485 | 0.02539 | -1.74270 | -9.2157 | 84.9078 |
| 5 5 | | | | | | | |
| 2 | -51300. | | | | | | |
| 3 . | 3293. | | | | | | |
| 4 | 19.13848 | 2.55046 | -0.37588 | 0.03702 | -1.04807 | -5.2626 | 78.9155 |
| 5 | | | | | | | |
| 6 | | | | | | | |
| 2 | -162600. | | | | | | |
| 3 | 2765. | | | . : | | · | |
| 4 | 21.26435 | 3.33827 | -0.91481 | 0.08746 | -2.04527 | -0.1818 | 78.9034 |
| 5 | | | | | | | |
| 6 | 1 05500 | | | | | | |
| 2 3 | -1.05500. 2556. | | | | | | |
| 4 | 17.92884 | 5.77349 | -1.58420 | 0.15200 | -2.30013 | -8.8788 | 70.8631 |
| 5 | 17.72001 | 4 ,,, 4 ,, | . , 50 120 | J,.J=V | | 0.107.00 | , 0,0001 |
| 6 | | | | | | | |
| | | | | | | | |

NOTE: Rows numbered 2 contain Δ Hf(g) for each species.
 Rows numbered 3 contain (H₂₉₈-H₀) (g) for each species.
 Rows numbered 4 contain a, b, c, d, e, H'and S' for gas phase.
 Rows numbered 5 and 6 are blank, since only gas phases are important for the above species.

FIG. 12 INPUT TAPE LISTING (B)

TWO CARDS ARE USED FOR THIS OPTION

Card No. 1

cc 2 punch: 1

Card No. 2

Start in cc 1, and punch as follows:

NOTE: \triangle on Card No. 2 represents a blank

Figure 13 - Input for Option (1)

TWO CARDS ARE USED FOR THIS OPTION

Card No. 1

cc 2 punch: 3

Card No. 2

cc 1, 2, 3 punch: identification number

cc 4 punch: g, 1, or s (phase)

cc 5, 14 punch: T_i

cc 15, 24 punch: T_f

cc 25, 34 punch: ΔT

NOTE: Fixed point: decimal point must be punched.

Figure 14 - Input Cards for Option (3)

APPENDIX A

Equations Used by the Program

Equation (1), Section II, defines $C_p(T)$ at a pressure of one atmosphere; and from Equation (2)

$$dT = 10^3 d\theta.$$

The enthalpy is then obtained by integrating

$$dH = C_p dT = 10^3 C_p d\Theta ; (A1)$$

thus

$$H = 10^{3}a\theta + \frac{10^{3}b\theta}{2} + \frac{10^{3}c\theta}{3} + \frac{10^{3}d\theta}{4} + \frac{10^{3}e}{4} + \frac{10^{3}e}{6} + H',$$
(A2)

where H' is the constant of integration.

Dividing Equation (A2) by $T = 10^3$ gives the enthalpy per degree. It is convenient to define

$$\frac{H - H_0}{T} = a + \frac{b\Theta}{2} + \frac{c\Theta}{3}^2 + \frac{d\Theta}{4}^3 - e^{\Theta^{-2}} + \frac{H! - H_0}{103}$$
 (A3)

Where the subscript o refers to the thermodynamic state at one atmosphere pressure and absolute zero of temperature. The integration constant used is an average value determined from

$$H' = \frac{1}{n} \frac{n}{1 = 1} H_1(T_1);$$
 (A4)

where $H_1(T_1)$ is the ith integration constant, obtained by substituting the ith temperature and enthalpy into Equation (A2) and n is the number of such substitutions.

For a reversible process at constant pressure the entropy change is

$$dS = \left(\frac{dH}{T}\right)_{P} \qquad , \tag{A5}$$

where S is the entropy. Using Equation (Al) and again taking the indefinite integral gives

where the integration constant S' is determined in the same way as H'.

Using the Gibbs free energy

$$G = H - TS$$

it is convenient to tabulate

$$-\left(\frac{G - G_{0}}{T}\right) = S - \left(\frac{H - H_{0}}{T}\right) \tag{A7}$$

where S_o has been arbitrarily chosen as zero.

Using Equations (1),(A3) and (A5) for $C_{\rm p}$, (H - H_o)/T and S respectively made the machine computations unnecessarily cumbersome. Simple algebraic manipulations (nesting) resulted in the more economical forms,

$$C_{p} = e/\Theta^{2} + a + \Theta \left[b + \Theta \left(c + d \Theta\right)\right] \tag{A8}$$

$$\frac{H - H_0}{T} = \frac{1}{\theta} \left[\frac{H'}{10^3} - \frac{e}{\theta} \right] + a + \theta \left[\frac{b}{2} + \theta \left(\frac{c}{3} + \frac{d\theta}{4} \right) \right]$$
 (A9)

$$S = S' - \frac{e0}{2}^{-2} + a \ln \theta + \theta \left[b + \theta \left(c/2 + \frac{\theta d}{3} \right) \right]$$
 (A10)

APPENDIX B

Fortran Listing

For those who wish to use it, the Fortran source program is given here. It is necessary only to punch the instructions on Hollerith cards, ignoring the blanks inserted before each Option.

Five comments occur in the listing. They are marked by a "C" in column one, and are in correct format. They will not interfere with the operation of the program, and are inserted to emphasize the Options. On page 5 the letter B occurring in column one identifies Boolean instructions. All others are in Fortran II language.

No control instructions are shown since they depend upon the system being used at a particular installation.

THERMODYNAMIC DATA PROGRAM

```
CHOOSE AN OPTION
      DIMENSION SPD(300,34), FORM(40), NREF(300,4), CP(5), A(5,5), C(5)
SXGAS ALF
            G
SXLIQ ALF
 31
      READI, NOPT
      FORMAT(12)
      IF(NOPT)19,30,2
      GO TO (3,13,3,1000), NOPT
 1000 GO TO 3
      IF(SPD(1,1))3001,3000,3001
 3
 3000 READ INPUT TAPE 7,4, (SPD(I,1), (FORM(J), J=1,40), SPD(I,2),
     1SPD(I,3),(NREF(I,K),K=1,4),I=1,40)
      FORMAT(F3.0,40F1.0,F10.0,211,314)
      DO 1001 I=41,300
      READ INPUT TAPE 7,4,SPD(I,1),(FORM(J),J=1,40),SPD(I,2),
     1SPD(I,3),(NREF(I,K),K=1,4)
      DO 1001 J=1,40
 1001 SPD(I,2)=SPD(I,2)+FORM(J)*SPD(J,2)
      READ INPUT TAPE 7,1002, ((SPD(I,J),J=4,34),I=1,300)
1002 FORMAT(5F10.0/5F10.0/7F10.0/7F10.0)
      REWIND 7
 3001 GO TO (6,6,22), NOPT
      BEGIN OPTION 1
\mathcal{C}
6
     READ 7, MO, NDAY, NYEAR
     FORMAT(12,213)
7
     PRINT 8, MO, NDAY, NYEAR
     FORMAT(111H1LISTING OF SPECIE-DATA INPUT (TAPE7) TO THEORETICAL PE
     1RFORMANCE PROGRAM
                                                                 12:1H/12:1
     ÎH/Î2)
PRÎNT 9
9
     FORMAT(103H1
                                                  M.P.
                                                             ΗV
                                                                       HM
             HF(298) (KCAL/KMOL)
    1
                                            REFERENCES/84H
                (K) (K)
                                    (KCAL/KMOL)
                                                      (G)
                                                                 (L)
    1 (S)/22H SPECIE ID.NO. MOL.WT.)
     NPAGE=0
     DO 11 I=1:300
     ID=SPD(I,1)
     PRINT 10, ID, SPD(I, 2), SPD(I, 7), SPD(I, 8),
    1SPD(I, 12), SPD(I, 13), SPD(I, 4), SPD(I, 5), SPD(I, 6), (NREF(I, J), J=1, 4)
                        13,F9.3,2F8.1,5F10.0,3H I1,2H, I3,2H, I3,2H, I
    FORMAT(9H
10
    13)
     CALL SYMBOL (I, 2, NCH)
     NPAGE=NPAGE+1
     TF(NPAGE-50)11,1005,1005
1005 NPAGE=0
     PRINT 9
```

```
CONTINUE
PRINT 1007
11
1007 FORMAT(83H1
                                         H(298)-H(0)
  - 1
                     COEFFICIENTS/102H SPECIE ID.NO. PHASE
                                                                (KCAL/KMOL
    1)
                                                D
                             В
                                      C
                                                         E
                                                                  K1
    1K2)
     N=0
     NPAGE=0
     DO 1008 I=1,300
     TEST G=0.
     TEST L=0.
     TEST S=0.
     ID=SPD(I,1)
    DC 1009 K=1,7
     TESTG=SPD(I,K+13)+TESTG
     TESTL=SPD(I,K+20)+TESTL
1009 TESTS=SPD(I,K+27)+TESTS
     IF(NPAGE-47)1021,1020,1020
1020 NPAGE=0
     PRINT 1007
1021 IF(TESTG)1012,1010,1012
1010 IF(TESTL)1014,1011,1014
1011 IF(TESTS)1016,1018,1016
1012 PRINT 1013, ID, SPD(I,9), (SPD(I,J+13),J=1,7)
1013 FORMAT(9H
                        I3:15H
                                 (G)
    15F9.5,F8.4,F9.4)
     NPAGE=NPAGE+1
     CALL SYMBOL (I,2,NCH)
     GO TO 1010
1014 PRINT 1015, ID, SPD(I, 10), (SPD(I, J+20), J=1,7)
1015 FORMAT(9H
                       I3,15H (L)
                                            F5•0•12H
    15F9.5,F8.4,F9.4)
     NPAGE=NPAGE+1
     CALL SYMBOL (1,2,NCH)
     GO TO 1011
1016 PRINT 1017, ID, SPD(I, 11), (SPD(I, J+27), J=1,7)
1017 FORMAT(9H
                        13,15H (S)
                                              F5.0,12H
    15F9.5,F8.4,F9.4)
     NPAGE=NPAGE+1
     CALL SYMBOL(I,2,NCH)
     GO TO 1018
1018 IF(TESTG+TESTL+TESTS) 1019,1008,1019
1019 N=N+1
1008 CONTINUE
      PRINT 2000,N
2000 FORMAT(22HODATA IS AVAILABLE FOR 14,9H SPECIES.)
      GO TO 31
       BEGIN OPTION 2
C
      READ 14
13
      FORMAT(37H COEFFICIENT DETERMINATION FOR
14
      READ 17, (CP(I), I=1,5), H,S
```

FORMAT(7F10.0)

17

```
A(1,1) = -3 \cdot 2040805
     A(1,2)=10.955440
     A(1,3) = -12.815569
     A(1,4)=8.7032594
     A(1,5) = -2.6390499
     A(2,1)=1.9376145
     A(2,2) = -7.2087899
     A(2,3)=10.775001
     A(2,4)=-8.0360433
     A(2,5)=2.5322178
     A(3,1) = -0.41001527
     A(3,2)=1.6033583
     A(3,3)=-2.7948590
     A(3,4)=2.4161851
     A(3,5) = -0.81466908
     A(4,1)=0.029156571
     A(4,2) = -.11770102
     A(4,3)=0.22712088
     A(4,4) = -0.22307338
     A(4,5)=0.08449696
     A(5,1)=2.6473247
     A(5,2) = -5.2323073
     A(5,3)=4.6083062
     A(5,4) = -2.8603279
     A(5,5)=0.8370043
     DO 15 I=1.5
     C(I)=0.
     DO 15 J=1.5
     C(I)=A(I,J)*CP(J)+C(I)
15
     XK1=3.*H-3.*C(1)-4.5*C(2)-9.*C(3)-20.25*C(4)+C(5)/3.
     XK2=S-1.09861*C(1)-3.*C(2)-4.5*C(3)-9.*C(4)+C(5)/18.
     PRINT 16
     FORMAT(1H1)
16
     PRINT 14
    PRINT 18, (CP(I), I=1,5), H,S,(C(I), I=1,5), XK1, XK2
117
                                                 1000
    FORMAT(71HO
                      MATCH TEMPERATURES
                                                          1600
                                                                    3000
18
                                                  CP 5F9.3/28H0
               5700/27H
    1 4500
                                                                       (H(3
    1000)-H(0))/3000 =F8.3/25H
                                                 S(3000) = F8.3/105H0
                                                               .D
                                                        1P7E14.5)
        Ε
                      Κ1
                                     K2/12H
    1
     GO TO 31
```

- BEGIN OPTION -1 \subset READ 20,TZ,TF,DT
- 19 FORMAT(3F10.0)
- 20
 - PRINT 21
- FORMAT (45H1THERMODYNAMIC FUNCTIONS FOR THE ABOVE SPECIE) GO TO 26

NOT/TR 62-84

```
C
       BEGIN OPTION 3
22
      READ 23 , NSP , PHASE , TZ , TF , DT
      FORMAT(13,1A1,3F10.0)
23
В
      TESTG=(PHASE+XGAS)*(-(PHASE*XGAS))
      TESTL=(PHASE+XLIQ)*(-(PHASE*XLIQ))
      IF(TESTG) 1022,1023,1022
 1022 IF(TESTL) 1024,1025,1024
 1023 J=13
      GO TO 1026
 1025 J=20
      GO TO 1026
 1024 J=27
 1026 DO 24 I=1.5
      K=I+J
 24
      C(I) = SPD(NSP *K)
      XK1=SPD(NSP,J+6)
      XK2=SPD(NSP;J+7)
      IF(TESTG) 1027,1030,1027
 1027 IF(TESTL) 1028,1029,1028
 1030 PRINT 1031
      GO TO 1034
 1029 PRINT 1032
      GO TO 1034
 1028 PRINT 1033
      GO TO 1034
                                                      (G))
 1031 FORMAT(39H1THERMODYNAMIC FUNCTIONS FOR
 1032 FORMAT(39H1THERMODYNAMIC FUNCTIONS FOR
                                                      (L))
 1033 FORMAT(39H1THERMODYNAMIC FUNCTIONS FOR
                                                      (5)1
 1034 CALL SYMBOL(NSP,30,NCH)
      GO TO 26
 26
      PRINT 27
                                                               (H-H(0))/T
                                              CP
      FORMAT (97HO
 27
                          T
                                     (G-G(0))/T)/97H
                                                             (K)
     1
     1 (KCAL/KMOL-K)
                             (KCAL/KMOL-K)
                                                   (KCAL/KMOL-K)
                                                                        (KC
     1AL/KMOL-K)/1H )
      NSTOP=1.+(TF-TZ)/DT
      DO 28 I=1,NSTOP
      XI = I
      T=TZ+(XI-1.)*DT
      THETA=T/1000.
      CPZ=C(1)+THETA*(C(2)+THETA*(C(3)+THETA*C(4)))+C(5)/THETA**2
      HOT=XK1/THETA+C(1)+.5*C(2)*THETA+.33333333*C(3)*THETA**2+.25
     1*C(4)*THETA**3-C(5)/THETA**2
      SZ=XK2+C(1)*LOGEF(THETA)+C(2)*THETA+.5*C(3)*THETA**2+.33333333
     1*C(4)*THETA**3-C(5)/2.*THETA**2
      GZ=HOT-SZ
      PRINT 29,T,CPZ,HOT,SZ,GZ
 28
                     F6.0.3H 1P4E20.5)
 29
      FORMAT(6H
      GO TO 31
 30
      CALL ENDJOB
```

DISTRIBUTION LIST

| | No. of Copies |
|--|------------------|
| SPIA (Distribution List) | 100 |
| Chief, Bureau of Naval Weapons Washington 25, D.C. Attn: DLI-3 Armed Services Technical Information Agency | 4 |
| Arlington Hall Arlington, Virginia | 10 |
| Indian Head, Maryland Attn: Technical Library | |
| Advanced Research Projects Agency Washington 25, D.C | 1 |
| China Lake, California Attn: Technical Library | 2 |
| Thermodynamics Division Attn: W. Evans | 1 |
| Propellant Sciences Division Menlo Park, California Attn: Dr. A. Amster | 1 |

CATALOGING INFORMATION FOR LIBRARY USE

| | | BIBLIOS | RAPHIC | BIBLIOGRAPHIC INFORMATION | | | |
|----------------------------|-------------|---------|-------------|--|-------|--------------|---------|
| DE. | DESCRIPTORS | CODES | ES | | | DESCRIPTORS | 92400 |
| source Naval Ordnance Lab | ab | NOLTR | l | SECURITY CLASSIFICATION AND CODE COUNT | | Inclassified | r r/011 |
| REPORT NUMBER NOL-TR-62-81 | | 620081 | | CIRCULATION LIMITATION | | | |
| REPORT DATE 15 May 1962 | | Ø562 | | CIRCULATION LIMITATION OR BIBLIOGRAPHIC | ATION | | |
| , | | | | BIBLIOGRAPHIC (SUPPL., VOL., ETC.) | 7 | | |
| | | SUBJEC | T ANALYS | SUBJECT ANALYSIS OF REPORT | | | |
| DESCRIPTORS | CODES | DESCRI | DESCRIPTORS | | CODES | DESCRIPTORS | CODES |
| Chemical | CHEM | | | | | | |
| Compounds | CMPU | | | | | | |
| Thermodynamic | THED | | | | | | |
| Data. | DATA | | | | | | |
| Magnetic | MAGC | | | | | | |
| Tape | TAPE | | | | | | |
| Digital | DIGI | | | | | | |
| Computer | COMP | | | | | | |
| Program | PROG | | | | | | |
| Theory | THEY | · | | | | | |
| Data collection | DATG | | | , | | | |
| | · | | | | | | |
| PRNC-NOL-5070/28 (5-62) | | | | | | | |

Burke, Bernard Burke, Bernard computer data computer data Processing Mathematical Thermodynam Thermodynam-Thermodynam-Thermodynam-Mathematical Processing Chemicals ic proper-Abstract card is Chemicals -Abstract card is unclassified ic proper-Project Project unclassified Title Title ties ď This report describes the production and use of a magnetic tape library of thermodynamic data. The tape is produced from a deck of punched cards. The data on each species include an identification number, coded references, formula, and atomic weight, the enthalpy change from O'K to 298,15°K, the standard heat of formation at 298,15°K, melting point and heat of fusion, boiling point and heat of raporization, coefficients giving the specific heat as a rational function of the temperature, and integration constants permitting calculation of enthalpy and entropy. weight the enthalpy change from O'R to 298,15°K, the standard heat of formation at 298,15°K, melting point and heat of vaporization, boiling point and heat of vaporization, coefficients giving the specific heat as a rational function of the temperature, and integration constants permitting salculation of enthalpy and entropy. Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-84)

A MAGNETIC TAPE LIBRARY OF THERMODYNAMIC DATA(U), by Bernard A. Burke and others. 15 May 1962, 25p, tables, charts, diags, Task PR-3. This report describes the production and use of a magnetic tape library of thermodynamic data. The tape is produced from a deck of punched cards. The data on each species include an identification number, Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-84)
A MAGNETIC TAFE LIBRARY OF THERMODYNAMIC DATA(U), by Bernard A. Burke and others.
IS May 1962, 25p. tables, charts, diags. UNCLASSIFIED UNCLASSIFIED Task PR-3.

Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-84)
A MAGNETIC TAPE LIBRARY OF THERMODYNAMIC DATA(U), by Bernard A. Burke and others.
15 May 1962, 25p, tables, charts, diags.
Task PR-3.

This report describes the production and use of a magnetic tape library of thermodynamic data. The tape is produced from a deck of punched cards. The data on each species include an identification number, coded references, formula, and atomic weight, the enthalpy change from O'K to 298 15°K, the standard heat of formation at 298 15°K, melting point and heat of furation fusion, boiling point and heat of vaporization, coefficients glyring the specific heat as a rational function of the temperature, and integration constants permitting calculation of enthalpy and entropy. UNCLASSIFIED

Burke, Bernard

Project

unclassified

computer data

Mathematical

- Processing

Title

Thermodynam -

ď

Chemicals -Thermodynam-

proper-

Abstract card is Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-84)
A MAGNETIC TAFE LIBRARY OF THERMODYNAMIC DATA(U), by Bernard A. Burke and others.
15 May 1962, 25p. tables, charts, diags.
Task PR-3.

This report describes the production and use of a magnetic tape library of thermodynamic data. The tape is produced from a deck of punched cards. The data on each species include an identification number coded references, formula, and atomic weight, the enthalpy change from O'K to 298.15°K, the standard heat of formation at 298.15°K, melting point and heat of fusion, boiling point and heat of fusion, coefficients giving the specific heat as a rational function of the temperature, and integration constants permitting calculation of enthalpy and entropy. UNCLASSIFIED

Chemicals -Thermodynam-Thermodynamic proper-H. ď ლ ლ

Burke, Bernard computer data - Processing Mathematical Title

Abstract card is unclassified

Project

properď Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-84)
A MAGNETIC TAFE LIBRARY OF THERMODYNAMIC DATA(U), by Bernard A. Burke and others.
15 May 1962, 25p. tables, obarts, diags. 15 May 196 Task PR-3

This report describes the production and use of a magnetic tape library of thermodynamic data. The tape is produced from a deck of punched cards. The data on each species include an identification number, coded references, formula, and atomic weight, the enthalpy change from O'k to 298 15°k, the standard heat of formation at 298 15°k, melting point and heat of fusion, boiling point and heat of vaporization, coefficients giving the specific heat as a rational function of the temperature, and integration constants permitting calculation of enthalpy and entropy. UNCLASSIFIED

Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-84)
A MAGNETIC TAFE LIBRARY OF THERMODYNAMIC DATA(U), by Bernard A. Burke and others.
15 May 1962, 25p, tables, charts, diags.
Task PR-3.

This report describes the production and use of a magnetic tape library of thermodynamic data. The tape is produced from a deck of punched cards. The dats on each species include an identification number, coded references formula, and atomic weight, the enthalpy change from O'K to 298.15'K, the standard heat of formation at 298.15'K, melting point and heat of fusion, boiling point and heat of raporization, coefficients giving the specific heat as a rational function of the temperature, and integration constants permitting calculation of enthalpy and entropy. UNCIASSIFIED

Thermodynam Thermodynam-Chemicals -

Burke, Bernard computer data Processing Mathematical litle ties

Abstract card is unclassified

Project

III.

Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-84)
A MAGNETIC TAPE LIBRARY OF THERMODYNAMIC DATA(U), by Bernard A. Burke and others. 15 May 1962, 25p, tables, charts, diags. Task PR-3.

coded references, formula, and atomic weight, the enthalpy change from O'K to 298 15°K, the standard heat of formation at 298.15°K, melting point and heat of raporization, boiling point and heat of raporization, coefficients giving the specific heat as a rational function of the temperature, and integration constants permitting calculation of enthalpy and entropy. This report describes the production and use of a magnetic tape library of thermodynamic data. The tape is produced from a deck of punched cards. The data on each species include an identification number, UNCLASSIFIED

Naval Ordnance Laboratory, White Oak, Md. (NOL technical report 62-84)
A MAGNETIC TAPE LIBRARY OF THERMODYNAMIC DATA(U), by Bernard A. Burke and others.
15 May 1962, 25p. tables, charts, diags.
Task PR-3.

Thermodynam-

ri*

Thermodynam

proper-

Chemicals -

This report describes the production and use of a magnetic tape library of thermodynamic data. The tape is produced from a deck of punched cards. The data on each species include an identification number, coded references, formula, and atomic weight, the enthalpy change from O'K to 296.15°K, the standard heat of formation at 298.15°K, melting point and heat of fusion, boiling point and heat of raporization, coefficients giving the specific heat as a rational function of the temperature, and integration constants permitting calculation of enthalpy and entropy.

Burke, Bernard

Project

Abstract card is

unclassified

computer data

Mathematical

ຕໍ

ties

Processing

Title

Burke, Bernard computer data Thermodynam-- Processing Mathematical Thermodynam -Chemicals ic proper-Project Title ties ij m ď ď

Abstract card is unclassified

UNCLASSIFIED

Burke, Bernard computer data Processing Thermodynam-Mathematical Thermodynam-Chemicals proper-Project ties ຕໍ

Abstract card is unclassified

UNCLASSIFIED

UNCLASSIFIED